


MULTI/JOINT® 3057 Plus Wide Range Flange adaptor, restraint, Uni/Fiksers



Model:


- Suitable for all kinds of pipe material
- Suitable for water and gas
- Ductile cast iron GGG45 body and clamping ring(s), acc. to EN-GJS-450-10
- RESICOAT® epoxy powder coating, according to GSK standards and EN 14901
- NBR or EPDM gasket, NBR acc. to EN 682 (-5°C up to +50°C), EPDM acc. to EN 681-1 (0°C up to +50°C)
- Angular deflection of max. 8° per socket at installation (based on the middle of the range)
- Stainless steel A4 quality (AISI 316) Uni/Fiksers
- Stainless steel A2 quality (AISI 304) or A4 quality (AISI 316) bolts, nuts and washers
- For restraint versions, on plastic pipes, the use of an insert stiffener (see accessories) is mandatory, check our technical information
- Hygiene protection included DN50 - DN600

| DN (mm) | Range 1 (mm) | Flange 3 (mm) | Drilling pat- tern | NBR / A2 Code | EPDM / A2 Code | Weight (kg) |
|------------|-----------------|------------------|-----------------------|--------------------|--------------------|----------------|
| 50 | 46 - 71 | 50 | PN16 | 709 355 210 | 709 355 610 | 5.600 |
| 65 | 63 - 90 | 60/65 | PN16 | 709 355 212 | 709 355 612 | 6.500 |
| 80 | 84 - 105 | 80 | PN16 | 709 355 214 | 709 355 614 | 6.500 |
| 100 | 104 - 132 | 100 | PN16 | 709 355 216 | 709 355 616 | 8.600 |
| 125 | 132 - 155 | 125 | PN16 | 709 355 218 | 709 355 618 | 13.000 |
| 150 | 154 - 192 | 150 | PN16 | 709 355 220 | 709 355 620 | 14.000 |
| 200 | 192 - 232 | 200 | PN10 | 709 355 224 | 709 355 624 | 21.700 |
| 200 | 192 - 232 | 200 | PN16 | 709 355 225 | 709 355 625 | 21.700 |
| 250 | 267 - 310 | 250 | PN10 | 709 355 228 | 709 355 628 | 31.100 |
| 250 | 267 - 310 | 250 | PN16 | 709 355 229 | 709 355 629 | 31.100 |
| 300 | 315 - 356 | 300 | PN10 | 709 355 232 | 709 355 632 | 40.500 |
| 300 | 315 - 356 | 300 | PN16 | 709 355 233 | 709 355 633 | 40.500 |
| 350 | 352 - 393 | 350 | PN10 | 709 355 236 | 709 355 636 | 52.100 |
| 350 | 352 - 393 | 350 | PN16 | 709 355 237 | 709 355 637 | 52.100 |
| 400 | 392 - 433 | 400 | PN10 | 709 355 238 | 709 355 638 | 65.100 |
| 400 | 392 - 433 | 400 | PN16 | 709 355 239 | 709 355 639 | 65.100 |
| 500 | 500 - 532 | 500 | PN10/PN16 | 709 355 274 | 709 355 674 | 89.000 |
| 600 | 605 - 637 | 600 | PN10/PN16 | 709 355 278 | 709 355 678 | 118.100 |

| DN (mm) | NBR / A4 Code | EPDM / A4 Code | Weight (kg) |
|------------|--------------------|--------------------|----------------|
| 50 | 709 355 010 | 709 355 310 | 5.600 |
| 65 | 709 355 012 | 709 355 312 | 6.500 |
| 80 | 709 355 014 | 709 355 314 | 6.500 |
| 100 | 709 355 016 | 709 355 316 | 8.600 |
| 125 | 709 355 018 | 709 355 318 | 13.000 |
| 150 | 709 355 020 | 709 355 320 | 14.000 |
| 200 | 709 355 024 | 709 355 324 | 21.700 |
| 200 | 709 355 025 | 709 355 325 | 21.700 |
| 250 | 709 355 028 | 709 355 328 | 31.100 |
| 250 | 709 355 029 | 709 355 329 | 31.100 |
| 300 | 709 355 032 | 709 355 332 | 40.500 |
| 300 | 709 355 033 | 709 355 333 | 40.500 |
| 350 | 709 355 036 | 709 355 336 | 52.100 |
| 350 | 709 355 037 | 709 355 337 | 52.100 |
| 400 | 709 355 038 | 709 355 338 | 65.100 |
| 400 | 709 355 039 | 709 355 339 | 65.100 |
| 500 | 709 355 074 | 709 355 374 | 89.000 |
| 600 | 709 355 078 | 709 355 378 | 118.100 |

Data sheet

valid from: 11/14/16



| DN (mm) | a (mm) | b (mm) | d (mm) | e (mm) | PN Water (bar) | PN Gas (bar) | No. of bolt holes flange |
|------------|-----------|-----------|-----------|-----------|-------------------|-----------------|--------------------------------|
| 50 | 179 - 194 | 164 | 100 | 3xM12 | 16.0 | 8 | 4 |
| 65 | 187 - 198 | 186 | 95 | 3xM12 | 16.0 | 8 | 4 |
| 80 | 183 - 197 | 204 | 115 | 3xM12 | 16.0 | 8 | 8 |
| 100 | 181 - 200 | 236 | 110 | 3xM16 | 16.0 | 8 | 8 |
| 125 | 196 - 214 | 264 | 120 | 4xM16 | 16.0 | 8 | 8 |
| 150 | 194 - 222 | 304 | 120 | 4xM16 | 16.0 | 8 | 8 |
| 200 | 224 - 251 | 354 | 140 | 6xM16 | 16.0 | 8 | 8 |
| 200 | 224 - 251 | 354 | 140 | 6xM16 | 16.0 | 8 | 12 |
| 250 | 260 - 295 | 432 | 170 | 6xM20 | 16.0 | 8 | 12 |
| 250 | 260 - 295 | 432 | 170 | 6xM20 | 16.0 | 8 | 12 |
| 300 | 283 - 318 | 490 | 170 | 8xM20 | 16.0 | 8 | 12 |
| 300 | 283 - 318 | 490 | 170 | 8xM20 | 16.0 | 8 | 12 |
| 350 | 326 - 364 | 534 | 245 | 8xM20 | 10.0 | 5 | 16 |
| 350 | 326 - 364 | 534 | 245 | 8xM20 | 10.0 | 5 | 16 |
| 400 | 356 - 395 | 574 | 275 | 10xM20 | 10.0 | 5 | 16 |
| 400 | 356 - 395 | 574 | 275 | 10xM20 | 10.0 | 5 | 16 |
| 500 | 365 - 390 | 715 | 275 | 10xM20 | 10.0 | 5 | 20 |
| 600 | 365 - 390 | 840 | 275 | 14xM20 | 10.0 | 5 | 20 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>