



Transition coupler PE/brass (CW617N)
Male thread

- PE 100 SDR 11 (ISO S5)
- 10 bar Gas / 16 bar Water
- With integral pipe fixation
- 4 mm pin connectors
- Limited path fusion indicators
- Supplied as a kit

R (inch)	d (mm)	Code	SP	Weight (kg)	d1 (mm)	L (mm)	s (mm)
½	20	720 920 756	1	0.187	31	110	30
1	20	720 920 754	1	0.344	44	124	40
¾	25	720 920 757	1	0.254	36	111	35
1	25	720 920 763	1	0.340	44	124	40
½	32	720 920 764	1	0.213	44	121	30
¾	32	720 920 765	1	0.268	44	122	35
1	32	720 920 758	1	0.340	44	117	40
1 ¼	32	720 920 766	1	0.489	54	135	50
1 ½	32	720 920 767	1	0.635	60	143	60
2	32	720 920 768	1	1.000	81	157	70
1	40	720 920 771	1	0.364	54	133	40
1 ¼	40	720 920 759	1	0.514	54	127	50
1 ½	40	720 920 772	1	0.645	66	143	60
2	40	720 920 773	1	0.961	81	157	70
1	50	720 920 776	1	0.367	66	141	40
1 ¼	50	720 920 777	1	0.554	66	143	50
1 ½	50	720 920 760	1	0.652	66	135	60
2	50	720 920 778	1	0.971	81	157	70
1	63	720 920 781	1	0.441	81	151	40
1 ¼	63	720 920 782	1	0.600	81	153	40
1 ½	63	720 920 783	1	0.712	81	153	60
2	63	720 920 761	1	0.943	81	147	70

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>