



## Transition coupler PE/brass (CW617N) With loose nut

- PE 100 SDR 11 (ISO S5)
- 16 bar Water
- With integral pipe fixation
- 4 mm pin connectors
- Limited path fusion indicators
- Delivered as a kit. Further combinations: modular system with threaded adapter and reductions
- Incl. flat gasket for water applications (KTW / WRAS approved)

d (mm)	Rp (inch)	Code	SP	Weight (kg)	d1 (mm)	d2 (mm)	L (mm)
25	¾	<b>720 910 007</b>	1	0.232	36	15	104
32	1	<b>720 910 008</b>	1	0.297	44	20	110
32	1 ½	<b>720 910 028</b>	1	0.480	44	22	114
50	1 ½	<b>720 910 010</b>	1	0.736	66	29	133
63	1	<b>720 910 021</b>	1	1.013	81	20	137
63	2	<b>720 910 011</b>	1	1.251	81	36	145

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>