



PROGEF Standard 3-Way ball valve type 543 Horizontal/T-port With fusion sockets metric

Model:

- Material: PP-H
- For easy installation and removal (valve end and union nut are compatible with type 546)
- Ball seals PTFE
- Pneumatic or electric actuator available separately
- Angle of operation 360° without turn limiter
- Turn limiter 90° enclosed, in different positions usable as a clip-on ring
- Integrated stainless steel mounting inserts
- Delivery status A-B-C opened, see flow scheme

d [mm]	DN [mm]	PN [bar]	kv-value ($\Delta p=1$ bar) [l/min]	EPDM Code	Weight [kg]	FPM Code	Weight [kg]
16	10	10	140	167 543 201	0.160	167 543 211	0.160
20	15	10	200	167 543 202	0.164	167 543 212	0.164
25	20	10	470	167 543 203	0.236	167 543 213	0.236
32	25	10	793	167 543 204	0.372	167 543 214	0.357
40	32	10	1290	167 543 205	0.631	167 543 215	0.609
50	40	10	1910	167 543 206	0.936	167 543 216	0.898
63	50	10	3100	167 543 207	1.822	167 543 217	1.857

d [mm]	D [mm]	H [mm]	H1 [mm]	H2 [mm]	L [mm]	L1 [mm]	L2 [mm]	L3 [mm]	L4 [mm]	L5 [mm]	L6 [mm]	M	z [mm]	z1 [mm]
16	50	57	28	8	110	77	72	36	25	32	45	6	82	41
20	50	57	28	8	112	77	72	36	25	32	45	6	82	41
25	58	67	32	8	129	97	85	43	25	39	58	6	97	49
32	68	73	36	8	146	97	98	49	25	39	58	6	110	55
40	84	90	45	9	170	128	118	59	45	54	74	8	132	66
50	97	97	51	9	193	128	135	68	45	54	74	8	151	76
63	124	116	65	9	244	152	176	88	45	66	87	8	188	94

d [mm]	closest inch [inch]
16	3/8
20	1/2
25	3/4
32	1
40	1 1/4
50	1 1/2
63	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
 Phone +41 -(0)52-631 1111
 e-mail: info.ps@georgfischer.com
 Internet: <http://www.gfps.com>