




SYGEF Standard silicone free Check valve type 561 With socket fusion spigots metric

Model:

- Material: PVDF / silicone free cleaned
- Sealing at a minimum water column of 2 m
- Designed for easy installation and removal
- Vibration free even at high flow velocity
- Flow-optimized return cone, double guided
- For vertical installation
- Compact installation length, same as ball valve type 546
- Z-length, end connectors and union nuts **not** compatible with type 360



Warning: please make sure the diameter is not reduced through welding beads (Danger of turbulences)

d [mm]	DN [mm]	PN [bar]	kv-value ($\Delta p=1$ bar) [l/min]	FPM Code	SP	Weight [kg]	D [mm]	L [mm]	L2 [mm]	closest inch [inch]
20	15	16	180	175 561 232	1	0.170	50	120	56	½
25	20	16	380	175 561 233	1	0.370	58	139	65	¾
32	25	16	460	175 561 234	1	0.400	68	150	71	1
40	32	16	850	175 561 235	1	0.670	84	170	85	1 ¼
50	40	16	1080	175 561 236	1	1.030	97	190	89	1 ½
63	50	16	1670	175 561 237	1	1.830	124	220	101	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
 Phone +41 -(0)52-631 1111
 e-mail: info.ps@georgfischer.com
 Internet: <http://www.gfps.com>