



Tapping saddle Monobloc version

- PE 100 SDR 11 (ISO S5)
- 10 bar Gas / 16 bar Water
- With integrated cutter to tap live mains under pressure
- Complete with lower part
- 4 mm pin connectors
- Limited path fusion indicators
- Long fusion outlet
- O-ring-sealed screw cap

d	d1	Code	SP	Weight	d2	H	H1	L	L1	z
(mm)	(mm)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
40	20	193 131 412	1	0.225	16	99	33	103	70	102
40	25	193 131 413	1	0.226	16	99	33	103	70	102
40	32	193 131 414	1	0.225	16	99	33	103	70	120
50	20	193 131 422	1	0.214	16	104	38	103	70	102
50	25	193 131 423	1	0.212	16	104	38	103	70	102
50	32	193 131 424	1	0.228	16	104	38	103	70	120
63	20	193 131 432	1	0.428	25	134	44	126	70	115
63	25	193 131 433	1	0.431	25	134	44	126	70	115
63	32	193 131 434	1	0.425	25	134	44	126	70	130

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>