



## SYGEF Standard adaptor nipple male thread metric R PN16

### Model:

- Material: PVDF
- With socket fusion spigot metric and BSP tapered male thread
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVDF
- Avoid stresses when installing and large changes in temperature

R	d	PN	Code	SP	Weight	z	L	s	
[inch]	[mm]	[bar]			[kg]	[mm]	[mm]	[mm]	
3/8	16	16	<b>735 910 505</b>	1	0.015	12	37	27	
1/2	20	16	<b>735 910 506</b>	1	0.025	25	53	32	
3/4	25	16	<b>735 910 507</b>	1	0.033	24	55	36	
1	32	16	<b>735 910 508</b>	1	0.056	22	57	46	
1 1/4	40	16	<b>735 910 509</b>	1	0.082	21	60	55	
1 1/2	50	16	<b>735 910 510</b>	1	0.113	19	63	65	
2	63	16	<b>735 910 511</b>	1	0.166	18	69	75	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland  
Phone +41 -(0)52-631 1111  
e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)  
Internet: <http://www.gfps.com>