



## Transition fittings PE/steel

- PE 100 SDR 11 (ISO S5)
- 8 bar Gas / 16 bar Water
- \*\*Suitable for 10 bar Gas / 16 bar Water
- Electrofusion weldable
- Steel pipe acc. to EN 10208-1, PE coated for corrosion resistance
- \* Steel pipe without plastic shroud

	d	d1	Code	SP	Weight	L	L1	L2
	(mm)	(inch)			(kg)	(mm)	(mm)	(mm)
*	20	¾	<b>775 641 502</b>	0	0.450	427	35	41
	25	¾	<b>775 641 507</b>	21	0.658	462	35	41
	32	1	<b>775 641 510</b>	18	0.988	462	35	44
	40	1 ¼	<b>775 641 514</b>	12	1.208	470	35	49
	50	1 ½	<b>775 641 518</b>	8	1.355	475	35	55
	63	2	<b>775 641 524</b>	6	2.011	480	35	63
	75	2 ½	<b>775 641 632</b>	2	2.983	545	35	70
	90	3	<b>775 641 636</b>	2	3.762	562	45	79
	110	3	<b>775 641 640</b>	2	4.381	580	45	82
	110	4	<b>775 641 641</b>	2	6.633	580	45	82
	125	4	<b>775 641 645</b>	2	6.833	584	45	87
	160	6	<b>775 641 655</b>	1	12.406	607	45	98
	180	6	<b>775 641 659</b>	1	11.935	605	45	105
	200	8	<b>775 642 664</b>	1	19.647	615	45	112
	225	8	<b>775 642 669</b>	1	20.154	620	45	120
	250	8	<b>775 642 665</b>	1	21.354	640	45	129
**	250	10	<b>775 642 666</b>	8	30.000	645	45	129
**	280	10	<b>775 642 673</b>	8	31.000	637	45	139
**	315	12	<b>775 642 672</b>	6	35.000	730	45	150
**	355	12	<b>775 642 675</b>	6	49.000	732	45	164
**	400	16	<b>775 642 678</b>	4	94.000	770	45	179

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>