



Elbow 90° ABS metric

- >d225 - maximum operating temperature: +40°C

d (mm)	PN (bar)	Code	SP	Weight (kg)	D (mm)	L (mm)	z (mm)	closest inch (inch)
20	16	729 100 106	10	0.010	26	27	11	½
25	16	729 100 107	10	0.018	31	33	14	¾
32	10	729 100 108	10	0.033	40	39	17	1
40	10	729 100 109	10	0.055	49	47	21	1 ¼
50	10	729 100 110	10	0.098	61	57	26	1 ½
63	10	729 100 111	10	0.186	76	72	33	2
75	10	729 100 112	5	0.300	90	84	40	2 ½
90	10	729 100 113	5	0.432	110	97	46	3
110	10	729 100 114	3	0.769	136	116	55	4
140	10	729 100 116	4	1.516	162	146	70	5
160	10	729 100 117	1	2.177	185	166	80	6
200	10	729 100 119	1	3.372	225	207	101	8
250	6	729 100 121	1	8.218	282	263	131	9

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>