


# Datasheet

## Threaded adaptor R PVC-U 3 diameters



d-d [mm]	R [inch]	PN	Code	SP	GP	kg	L1 [mm]	L2 [mm]	L3 [mm]	H [mm]	O [mm]
16 - 16	3/8	16	<b>RV0AMP12A</b>	100	600	0.008		14	11.4	36	22
16 - 20	3/8	16	<b>RV0AMP16A</b>	100	500	0.009	14.0	16	11.4	40	24
16 - 20	1/2	16	<b>RV0AMP16B</b>	100	400	0.010	14.0	16	15.0	43	24
20 - 25	3/8	16	<b>RV0AMP20A</b>	100	300	0.014	16.0	19	11.4	43	30
20 - 25	1/2	16	<b>RV0AMP20B</b>	100	300	0.014	16.0	19	15.0	46	30
20 - 25	3/4	16	<b>RV0AMP20C</b>	100	300	0.015	16.0	19	16.3	47	30
25 - 32	1/2	16	<b>RV0AMP25B</b>	100	200	0.025	19.0	22	15.0	49	36
25 - 32	3/4	16	<b>RV0AMP25C</b>	100	200	0.026	19.0	22	16.3	50	36
25 - 32	1	16	<b>RV0AMP25D</b>	100	200	0.029	19.0	22	19.1	53	36
32 - 40	3/4	16	<b>RV0AMP32C</b>	10	140	0.036	22.0	26	16.3	54	46
32 - 40	1	16	<b>RV0AMP32D</b>	10	120	0.040	22.0	26	19.1	57	46
32 - 40	1 1/4	16	<b>RV0AMP32E</b>	10	100	0.049	22.0	26	21.4	60	46
40 - 50	1	16	<b>RV0AMP40D</b>	90	-	0.070	26.0	31	19.1	64	55
40 - 50	1 1/4	16	<b>RV0AMP40E</b>	50	-	0.075	26.0	31	21.4	67	55
40 - 50	1 1/2	16	<b>RV0AMP40F</b>	80	-	0.074	26.0	31	21.4	67	55
50 - 63	1 1/4	16	<b>RV0AMP50E</b>	50	-	0.116	31.0	38	21.4	74	65
50 - 63	1 1/2	16	<b>RV0AMP50F</b>	110	-	0.113	31.0	38	21.4	74	65
50 - 63	2	16	<b>RV0AMP50G</b>	100	-	0.125	31.0	38	25.7	78	65
63 - 75	1 1/2	16	<b>RV0AMP63F</b>	35	-	0.145	38.0	44	21.4	80	80
63 - 75	2	16	<b>RV0AMP63G</b>	70	-	0.150	38.0	44	25.7	84	80
63 - 75	2 1/2	16	<b>RV0AMP63H</b>	50	-	0.170	38.0	44	30.2	91	80
75 - 90	2	16	<b>RV0AMP75G</b>	54	-	0.270	44.0	51	25.7	94	95
75 - 90	2 1/2	16	<b>RV0AMP75H</b>	60	-	0.275	44.0	51	30.2	99	95
75 - 90	3	16	<b>RV0AMP75I</b>	36	-	0.285	44.0	51	33.3	102	95
90 - 110	2 1/2	16	<b>RV0AMP90H</b>	25	-	0.470	51.0	61	30.2	110	115
90 - 110	3	16	<b>RV0AMP90I</b>	25	-	0.486	51.0	61	33.3	113	115
90 - 110	4	16	<b>RV0AMP90L</b>	16	-	0.485	51.0	61	39.3	118	115
110 - 125	3	10	<b>RV0AMP91I</b>	40	-	0.490	61.0	66	33.3	115	130
110 - 125	4	10	<b>RV0AMP91L</b>	32	-	0.492	61.0	66	39.3	120	130
110 - 125	5	10	<b>RV0AMP91N</b>	32	-	0.535	61.0	66	40.0	120	130
125 - 140	5	10	<b>RV0AMP92N</b>	24	-	0.740	69.0	71	74.0	145	

PF 2 01 951 011